

4730 Mechanics 3

1	(i) $T = (1.35mg)(3 - 1.8) \div 1.8$ [$0.9mg = ma$] Acceleration is $8.82ms^{-2}$	B1 M1 A1		For using $T = ma$
	(ii) Initial EE = $(1.35mg)(3 - 1.8)^2 \div (2 \times 1.8)$ [$\frac{1}{2}mv^2 = 0.54mg$] Speed is $3.25ms^{-1}$	B1 M1 A1	3	For using $\frac{1}{2}mv^2 = \text{Initial EE}$
2	(i)	M1		For using NEL vertically
	Component is $8\sin 27^\circ$	A1		
	Component is $2.18ms^{-1}$	A1	3	
	(ii) Change in velocity vertically = $8\sin 27^\circ(1 + e)$	B1ft		ft $8\sin 27^\circ$ + candidate's ans. in (i) For using $ I = m \times \text{change in velocity}$
	$ I = 0.2 \times 5.81$	M1		ft incorrect ans. in (i) providing both M marks are scored.
	Magnitude of Impulse is 1.16 kgms^{-1}	A1ft	3	
3				For using the principle of conservation of momentum in the i direction
	$0.8 \times 12 \cos 60^\circ = 0.8a + 2b$	M1 A1		
	$0.75 \times 12 \cos 60^\circ = b - a$	M1 A1		For using NEL
	$[4.8 = 0.8a + 2(a + 4.5)]$ $a = -1.5$	DM1 A1		For eliminating b; depends on at least one previous M mark
	Comp. of vel. perp. to l.o.c. after impact is $12\sin 60^\circ$	B1		
	The speed of A is $10.5ms^{-1}$	M1 A1ft		For correct method for speed or direction ft $v^2 = a^2 + 108$
	Direction of A is at 98.2° to l.o.c.	A1ft	10	Accept $\theta = 81.8^\circ$ if θ is clearly and appropriately indicated; ft $\tan^{-1} \theta = (12\sin 60^\circ)/ a $

4	(i)	$[mg \sin \alpha - 0.2mv = ma]$	M1		For using Newton's second law
		$5 \frac{dv}{dt} = 28 - v$	A1		AG
		$[\int \frac{5}{28 - v} dv = \int dt]$	M1		For separating variables and integrating
		$(C) - 5 \ln(28 - v) = t$	A1		
			M1		For using $v = 0$ when $t = 0$
		$\ln[(28 - v)/28] = -t/5$	A1ft		ft for $\ln[(28 - v)/28] = t/A$ from $C + A \ln(28 - v) = t$ previously
		$[28 - v = 28e^{-t/5}]$	M1		For expressing v in terms of t
		$v = 28(1 - e^{-t/5})$	A1ft	8	ft for $v = 28(1 - e^{-t/5})$ from $\ln[(28 - v)/28] = t/A$ previously
	(ii)				For using $a = (28 - v(t))/5$ or $a = d(28 - 28e^{-t/5})/dt$ and substituting $t = 10$.
		$[a = 28e^{-2}/5]$	M1		ft from incorrect v in the form $a + be^{ct}$ ($b \neq 0$); Accept $5.6/e^2$
		Acceleration is $0.758ms^{-2}$	A1ft	2	

5	(i)				For taking moments about B or about A for the whole or For taking moments about X for the whole and using $R_A + R_B = 280$ and $F_A = F_B$
		$1.4R_A = 150 \times 0.95 + 130 \times 0.25$ or	M1		
		$1.4R_B = 130 \times 1.15 + 150 \times 0.45$ or			
		$1.2F - 0.9(280 - R_B) + 0.45 \times 150 - 1.2F + 0.5R_B$	A1		
		$-0.25 \times 130 = 0$			
		$R_A = 125N$	A1		AG
		$R_B = 155N$	B1	4	
	(ii)		M1		For taking moments about X for XA or XB
		$1.2F_A = -150 \times 0.45 + 0.9R_A$ or			
		$1.2F_B = 0.5R_B - 130 \times 0.25$	A1		
		F_A or $F_B = 37.5N$	A1ft		$F_B = (1.25R_B - 81.25)/3$
		F_B or $F_A = 37.5N$	B1ft	4	
	(iii)	Horizontal component is $37.5N$ to the left	B1ft		ft $H = F$ or $H = 56.25 - 0.75V$ or $12H = 325 + 5V$
		$[Y + R_A = 150]$	M1		For resolving forces on XA vertically
		Vertical component is $25N$ upwards	A1ft	3	ft $3V = 225 - 4H$ or $V = 2.4H - 65$

6	(i)				For applying Newton's second law
		$[0.36 - 0.144x = 0.1a]$	M1		
		$\ddot{x} = 3.6 - 1.44x$	A1		
		$\ddot{y} = -1.44y \rightarrow \text{SHM}$ or	B1		
		$d^2(x - 2.5)/dt^2 = -1.44(x - 2.5) \rightarrow \text{SHM}$	M1		For using $T = 2\pi/n$
		Of period 5.24s	A1	5	AG
	(ii)	Amplitude is 0.5m	B1		
		$0.48^2 = 1.2^2(0.5^2 - y^2)$	M1		For using $v^2 = n^2(a^2 - y^2)$
		Possible values are 2.2 and 2.8	A1ft		
			A1	4	
	(iii)	$[t_0 = (\sin^{-1}0.6)/1.2; t_1 = (\cos^{-1}0.6)/1.2]$	M1		For using $y = 0.5\sin 1.2t$ to find t_0 or $y = 0.5\cos 1.2t$ to find t_1
		$t_0 = 0.53625 \dots$ or $t_1 = 0.7727 \dots$	A1		Principal value may be implied
	(a)	$[2(\sin^{-1}0.6)/1.2 \text{ or } (\pi - 2\cos^{-1}0.6)/1.2]$	M1		For using $\Delta t = 2t_0$ or $\Delta t = T/2 - 2t_1$
		Time interval is 1.07s	A1ft		ft incorrect t_0 or t_1
	(b)				From $\Delta t = T/2 - 2t_0$ or $\Delta t = 2t_1$; ft 2.62 – ans(a) or incorrect t_0 or t_1
		Time interval is 1.55s	B1ft	5	

7	(i)		M1		For using KE gain = PE loss
		$\frac{1}{2}mv^2 = mga(1 - \cos\theta)$	A1		
		$aw^2 = 2g(1 - \cos\theta)$	B1	3	AG From $v = wr$
	(ii)				For using Newton's second law radially (3 terms required) with accel = v^2/r or w^2r
		$mv^2/a = mg\cos\theta - R$ or $maw^2 = mg\cos\theta - R$	M1		
			A1		
		$[2mg(1 - \cos\theta) = mg\cos\theta - R]$	DM1		For eliminating v^2 or w^2 ; depends on at least one previous M1
		$R = mg(3\cos\theta - 2)$	A1ft	4	ft sign error in N2 equation
	(iii)				For using Newton's second law tangentially or differentiating
		$[mg\sin\theta = m(\text{accel.})$ or $2a(\dot{\theta})\ddot{\theta} = 2g\sin\theta(\dot{\theta})]$	M1		$aw^2 = 2g(1 - \cos\theta)$ w.r.t. t
		Accel. ($=a\ddot{\theta}$) = $g\sin\theta$	A1		
		$[\theta = \cos^{-1}(2/3)]$	M1		For using $R = 0$
		Acceleration is 7.30ms^{-2}	A1ft	4	ft from incorrect R of the form $mg(A\cos\theta + B)$, $A \neq 0$, $B \neq 0$; accept $g\sqrt{5}/3$
	(iv)				For using rate of change = $(dR/d\theta)(d\theta/dt)$
		$dR/dt = (-3mg\sin\theta)\sqrt{2g(1 - \cos\theta)}/a$	M1		ft from incorrect R of the form $mg(A\cos\theta + B)$, $A \neq 0$
			A1ft		
			M1		For using $\cos\theta = 2/3$
		Rate of change is $-mg\sqrt{\frac{10g}{3a}}\text{Ns}^{-1}$			Any correct form of \dot{R} with $\cos\theta = 2/3$ used; ft with θ from incorrect R of the form $mg(A\cos\theta + B)$, $A \neq 0$, $B \neq 0$
			A1ft	4	